

Control of System Software as per clause 5.18 of API16D edition 3rd

Rev	Reason of Change	Date	Prepared by	Reviewed by	Approved by	Status
1	Initial release	17.01.2019	SKG	USR	AS	Released
2	FMEA ammend	20-12-2024	NK	USR	JG	Release



Control of System Software as per clause 5.18 of API 16D edition 3rd.

1. Purpose

1.1. The scope of this procedure for BOP control system software design verification, installation and validation procedure. It also includes software FMEA and its maintenance.

2. Reference documents

2.1. API 16D

3. General requirement as per clause 5.18.1 of API16D

- 3.1. The control system software requirement per customer should be fulfilled. The proof of fulfilment should be verified, documented and provided to customer. The Proof of fulfilment is to be covered through **Factory Acceptance Test (FAT)** procedure for individual control unit.
- 3.2. The reference standards and process involved in the design and development of the system software is to be followed properly.
- 3.3. The processes involved in Design and Development beside upgradation of software is to be documented with traceability records and revision no. (eg: The PLC input and Output addressing to be preserved with identification no.)
- 3.4. The software is password protected to prevent its use by the person who do not have proper knowledge of design and development of software.
- 3.5. Software used- 10.0 PAC Machine Edition Professional Development Suite or simatic step 7 version 19.0
programming language - Ladder Diagram OR LD
Standard used- IEC 61131-3
programmable logic controller (PLC) used – EMERSON or SIEMENS

4. Classification of Software Life Cycle Process as per clause 5.18.2 of API 16D

Software life cycle is process by which software is developed, deployed and successfully installed on the control unit.

The software life cycle process shall include the following:

- 4.1. Software functional specification



	SARA SAE ENGINEERING SPECIFICATION	
	Section: SES 26 – 853	
	Issue: "A"	Rev No: "2"
	Eff. Date: 20-12-2024	Page: 3 of 31

- 4.2. Software Design and Development
- 4.3. Software Verification and Validation
- 4.4. Software Production and Maintenance

5. Software functional Specification per clause 5.18.3 of API16D

- 5.1. All the functional specification is documented per clause **5.18.3.1 of API16D** in **Annexure 'A'** of SARA SAE/R&D-TP-0198
- 5.2. All the additional functional specification is documented per clause **5.18.3.2 of API16D** in **Annexure 'A'** of SARA SAE/R&D-TP-0198
- 5.3. Technical requirement of system capabilities represent in checklist and documented per clause **5.18.3.3 of API 16D** in **Annexure 'A'** of SARA SAE/R&D-TP-0198
- 5.4. Software functional specification review format documented per clause **5.18.3.4 of API16D** in **Annexure 'B'** of SARA SAE/R&D-TP-0198

6. Software Design and Development as per clause 5.18.4 of API 16D

- 6.1 Software design review should be conducted and tested at different stages as per clause **5.18.4.1 of API 16D**. All panel should be tested individually at preliminary , critical and final design stages and documented in **Annexure 'B'** of SARA SAE/R&D-TP-0198
- 6.2 The system design architecture drawing includes system topology,logic flow diagram as per clause **5.18.4.2 of API16D** and documented in **Annexure 'C'** of SARA SAE/R&D-TP-0198
- 6.3 Failure modes effect analysis (FMEA) per clause **5.18.4.3 of API16D** is to be carried out and documented in **Annexure 'G'** of SARA SAE/R&D-TP-0198
- 6.4 The design and development of software code should follow per IEC standard.
- 6.5 The software code includes the design and development of programming software that it could be understood and implemented by other relevant software engineer. as per clause **5.18.4.5 of API16D**
- 6.6 Softcopy of installation and development tools guide should be documented as per clause **5.18.4.6 of API16D** (manufacturer, software platform and version) .
- 6.7 Software itself enables developer to provide the possible solution if some error occurred. Generally, this is possible by using PLC software inbuilt.

7. Software Validation and Verification as per clause 5.18.5 of API 16D



- 7.1 Software verification and validation for BOP control system enable user to provide local, system and global effect per **Annexure 'G'** of SARA SAE/R&D-TP-0198
- 7.2 PLC Software enable and validate all the operational logic, instructions and communication parameter
- 7.3 The Individual software component testing is to be documented in **Annexure 'B'** of SARA SAE/R&D-TP-0198
- 7.4 Assembled panel testing performance is to be documented in **Annexure 'B'** of SARA SAE/R&D-TP-0198
- 7.5 Every line of code and corresponding logic path having statement true/false is to be executed at least once. This facility is available in plc software itself.
- 7.6 The Software integration level test is to be done to test the complete integrated Modules beside testing individually before integrating the components. Once all the modules are tested, software integration testing is done by integrating all the modules and the system as a whole is tested, and the result is to be documented in **Annexure 'B'**
- 7.7 The testing shall be performed with BOP control unit per **Factory Acceptance Test procedure (FAT)**.
- 7.8 In case of failure of the communication between the panels provision of communication fail alarm is to be incorporated through software.
- 7.9 Every line of code and logic path shall be tested as part of white box testing as per **Annexure 'E'**
- 7.10 Single Unit functionality which provides input v/s output shall be treated as black box testing as per **Annexure 'B'**, **Annexure 'F'** & **Annexure 'A'**

8. Software Production and Maintenance as per clause 5.18.6 of API 16D

- 8.1. The modification to existing software shall be reviewed and documented in softcopy (retain old program and modify program)
- 8.2. The PLC software is developed, deployed and installed under software development life cycle (SDLC) with traceability records.
- 8.3. The Updated software if amended is to be reviewed and documented in softcopy.
- 8.4. The software shall be recorded with its current revision having all the details i.e. date, time, reason, unique identification and name of person conducting change. Software Back-up is to be stored in safe location separately, in **Annexure 'H'**
- 8.5. Risk assessment is not to be carried out for software security being external excess and internet accessibility to software.





SARA SAE ENGINEERING SPECIFICATION

Section: SES 26 – 853

Issue: "A"

Rev No: "2"

Eff. Date: 20-12-2024

Page: 5 of 31


8.6. The latest version of manufacturer supplied software platform is to be used to create PLC Programme for control unit. Date of incorporation of latest software platform is to be recorded.




Annexure 'C'


SOFTWARE FUNCTION PROCEDURE FOR PLC SLAVE PANEL

OBJECTIVE: TO CREATE A BLOCK DIAGRAM WHICH WILL SHOW HOW A VALVE CAN BE OPERATED FOR OPEN & CLOSE FUNCTIONS

BASIC LAYOUT: (A) FOR OPEN FUNCTION






NOW THESE THREE BITS WILL HAVE TO RESET BY ACKNOWLEDGE (ACK.) BUTTON ON THE SLAVE MODULE.



(THIS WILL BE BECAUSE THERE WILL BE NO SIGNAL FROM MASTER PANEL FURTHER)




BASIC LAYOUT: (B) FOR CLOSE FUNCTION




NOW THESE THREE BITS WILL HAVE TO RESET BY ACKNOWLEDGE (ACK.) BUTTON ON THE SLAVE MODULE.






(THIS WILL BE BECAUSE THERE WILL BE NO SIGNAL FROM MASTER PANEL FURTHER)




Annexure 'D'

TROUBLESHOOTING GUIDE FOR SMART CONTROL PLC PANEL

FAULT - 1: ON TURNING ON THE PANEL, NOTHING COMES UP





FAULT - 2: AC –DC CONVERTER (SMPS) IS SUSPECTED TO RECEIVE MAINS SUPPLY & CONVERT TO DC



FAULT - 3: PROBLEMS OBSERVED ON PLC MODULES

- POWER SUPPLY
- CPU MODULE
- INPUT MODULE/s
- OUTPUT MODULE/s
- ANALOG I/O





B

3.10 ANALOG INPUT & OUTPUT MODULES ARE USED TO SENSE & TRANSMIT THE SIGNAL FROM TRANSDUCER

3.10.1 ANALOG INPUT MODULE INSTALLED ON MASTER RECEIVES SIGNAL FROM TRANSDUCERS & FURTHER SENDS THE DIGITAL VALUES TO THE DIGITAL METERS OR SCREENS INSTALLED ON THE SLAVE PANELS.

3.10.2 IMP: TRANSDUCER GIVES SIGNAL TO THE INPUT ANALOG MODULE ON THE MASTER PANEL IN THE CURRENT RANGE FROM 4 – 20 MILLI AMPERES I.E. 0 PRESSURE SET AT 4 MILLI AMP. & MAXIMUM PRESSURE SET AT 20 MILLI AMPERES.



FAULT- 5: NO COMMUNICATION BETWEEN MASTER PANEL & SLAVE PANELS.

IF FAULT IS SUCH THAT THERE IS NO COMMUNICATION AMONG THE PANELS .MAKE THE FOLLOWING CHECKS ONE BY ONE.

4.5.1 STEP 1

- > FIRSTLY VERIFY THAT ALL THE PANELS ARE SWITCHED ON
- > NOW ENSURE THAT ALL PANELS ARE IN RUN MODE.
- > TO CHECK WHETHER PANELS HAVE PROGRAM STORED IN EACH OF THEM, PRESS LAMP TEST BUTTON (LTB).
- > NOW IF WORKING ON PANELS WITH TOUCH SCREEN, ON PRESSING LTB, ALL LIGHTS WILL COME UP, IF PROGRAM IS STORED IN CPU MODULE.
- > IF WORKING WITH DIGITAL GAUGS, ON PRESSING LTB, LIGHTS WILL COME UP FOR MOTOR RUN & ALARM INDICATION.
- > NOW IF ABOVE CONDITION IS NOT SATISFIED THEN PROGRAM NEEDS TO BE STORED INTO THE PLC CPU MODULE.
SEE STEPS 3.7.1 -3.7.3
- > DURING THIS PROCESS ALSO MAKE SURE THAT I/P BIT IS GENERATED EVERYTIME LAMP TEST IS PRESSED.ELSE CHECK WIRE CONNECTION FOR LAMP TEST.

4.5.2 STEP 2

- > CHECK THE PLUG & SOCKET OF COMM. CONNECTOR TO BE LOOPED PROPERLY. IF FOUND LOOSE TIGHTEN THEM.
- > CABLE WIRES MUST BE FIRMLY CRIMPPED INTO PINS OF SOCKET, IF FOUND LOOSE AGAIN DISMANTLE IT AND CRIMP.
- > COMMUNICATION CABLE TO BE CHECKED FOR ANY BREAKAGES OR TAMPERED IN BETWEEN THEIR LENGTHS.
- > IF CABLE FOUND NOT FIT FOR USE, REPLACE THE COMPLETE CABLE.
- > CHECK THE WIRING CONNECTIONS OF GENIUS BUS CONTROLLER
- > IF USING SERIES 90-30 PLC SEE THAT SER 1, SER 2 FROM MASTER IS CONNECTED IN SERIES WITH SLAVES & SHLD IN & SHLD OUT ARE LOOPED AS PER DRAWING.
- > IF WORKING WITH VERSA MAX PLC MODULES TWO POSSIBILITIES EXIST.
IF WORKING ON WIRED ETEHRNET COMM. FOLLOW FIRST FOUR STEPS AS ABOVE.
- IF WORKING WITH WIRELESS MODULE ENSURE FOR ACCURATE CONNECTIONS B/W PLC TO SWITCH & SWITCH TO ANTENNA, SEE OPERATIONAL MANUALS FOR DAWINGS.





SARA SAE ENGINEERING SPECIFICATION

Section: SES 26 – 853

Issue: "A"

Rev No: "2"

Eff. Date: 20-12-2024

Page: 17 of 31

FAULT- 6: NO READINGS IS OBSERVED ON DIGITAL GAUGES

6.1 DIGITAL METERS (DM) ARE USED TO SHOW PRESSURE READINGS OF ACCUMULATOR, MANIFOLD, ANNULAR & RIG AIR PRESSURE.POSSIBILITY EXIST THAT THESE DIGITAL METERS (DM) WOULD NOT SHOW READINGS OR WOULD NOT WORK AS DESIRED.FOLLOW THESE TROUBLE SHOOTING STEPS

6.1.1

IF DM IS NOT SHOWING ANY READINGS FIRSTLY CHECK THE 24 VDC SUPPLY ON IT.

NOW CHECK THE CONNECTIONS BETWEEN THE ANALOG OUTPUT MODULE & THE DM WITH THE HELP OF MULTIMETER MAKE SURE YOU SWITCH OFF THE PANEL EVERYTIME, BEFORE CHECKING THE CONTINUITY.CONNECTIONS HAS TO BE ACCORDING TO ELECTRICAL DRAWINGS ATTACHED WITH THE MANUALS.

6.1.2

UPTILL NOW IF THINGS ARE OK, THEN CHECK THE INPUT SIGNAL RECEIVED FROM MASTER PANEL. TRANSDUCER PROVIDES THE OUTPUT SIGNAL IN THE RANGE FROM 4 – 20milli Amp. TRANSDUCER SIGNAL IS FED TO ANALOG INPUT MODULE WHICH READS THE PRESSURE VALUES & SENDS IT TO ANALOG OUTPUT MODULE FOR FURTHER DISPLAY TO DM. CROSS CHECK ALL THE CONNECTIONS WITH ELECTRICAL DRAWINGS & TRANSDUCERS FOR ANY LEAKAGES.

6.1.3

AFTER FOLLOWING THE FIRST TWO STEPS, IF ALL THE CONNECTIONS & SETTINGS ARE FOUND OK & STILL NO READING IS DISPLAYED ON DM WHEN THERE IS READINGS ON ANALOG GAUGES ON UNIT, PROGRAM THE GAUGE AS PER THE PROGRAMMING STEPS ATTACHED ABOVE.

6.1.4

ANOTHER FAULT THAT A DM CAN HAVE IS, GAUGES SHOWS CORRECT READINGS BUT WHEN PRESSURE DROPS, NO CUTOFF RELAY IS ACTIVATED FOR ALARM SIGNAL TO BLOW & INDICATE LOW PRESSURE. IN SUCH CASE FIRSTLY CHECK THE CONNECTIONS FOR ALARM ON DM AS PER DRAWINGS. IF CONNECTIONS ARE FOUND OK AND STILL ALARM NOT COMING, THEN MAKE THIS VISUAL CHECK, OBSERVE SETPRESSURE INDICATOR (SP) OUT OF SP1/SP2/SP3/SP4 HIGHLIGHTED RED ON THE RIGHT PORTION OF THE DM .IT SHOWS THAT THE PARTICULAR RELAY IS ACTIVATED FOR THE ALARM TO ACTIVATE.IF THIS SP INDICATION IS NOT VISIBLE,



Software	Qty	Description	Serial Number	Legacy Serial Number	Contract Level	Contract End	Activation Code	Action
----------	-----	-------------	---------------	----------------------	----------------	--------------	-----------------	--------

PAC Machine Edition	1	Machine Edition v10.0 Professional Development Suite 700 Points	7-43959401-003-001	7-43915201-003-001-003-002	None		6be0106c-db65-446a-ae0e-b2a4d4d12a9e	Updated
---------------------	---	---	--------------------	----------------------------	------	--	--------------------------------------	---------

Status	Family	Product	Version	Number of lic...	License key	License number	Standard licens...	License type	Validity	Article No.
✓	SIMATIC STEP 7	STEP 7 Basic	19.0	1	SIFL57BASB1900	10411000916198869631	Floating	Unlimited	Unlimited	

Objectives

Programming Languages are LD, SFC, FBD, CFC and ST.

Ladder Diagram remains popular and easier because of its graphical nature so we used LD (Ladder Diagram).

As with lawn power tools, it is most efficient to use the best programming language for the application, to avoid the complexity of driving the square application peg into the round tool hole. With IEC 61131-3 programming languages, PLC programming and maintenance are enhanced when the strengths of all the languages are used.

Programming languages: LD, SFC, FBD, CFC and ST

the strengths and best applications Ladder Diagram (LD) and Sequential Function Chart (SFC).

“Which IEC 61131-3 Programming Language is best? Part 2” will discuss Function Block Diagram (FBD), Continuous Function Chart (CFC), Structured Text (ST), and how they can be mixed and matched for optimal results.

What is Ladder diagram (LD) programming?

Ladder diagram programming or LD, traces its history back some 100 years to relay ladder logic (RLL), which was created to describe systems of electrical components such as relays, timers and motors. In the early days of automation, when PLCs were replacing relays and timers, it made perfect sense to create a programming language familiar to the user base and similar to the tool it was replacing. Unfortunately, as controllers became more capable and evolved past relays and timers, the original LD language was pressed into service it was never intended for and was poorly suited.

This situation was exacerbated by the slow pace at which PLC vendors provided new languages better suited to PLC and programmable automation controllers (PAC) applications. This was particularly true with controllers originating in North America, which explains the global differences in the enduring popularity of LD.

Strengths of LD programming

The strength of LD and the key to its enduring popularity is its graphical nature. Of all the generalizations we can say about engineers, it is safe to say engineers tend to be graphically oriented. (Who among us can effectively communicate without paper and pencil, or a white board?) Early on, most LD



programming alternatives were text-based languages that did not resonate with engineers' graphical nature. This led to further reluctance to move on from LD. Fortunately, that situation is changing.

LD remains a great language for which it was originally intended – complex Boolean logic. Staying within this realm, LD logic is simple to design and simple to debug. Figure 3 illustrates this point by showing the same Boolean logic in several IEC 61131-3 languages. Say we are expecting "Inspect" to be TRUE. How easy is it to determine why the result is not as expected? In LD, the answer is quickly determined by observing where the path of solid blue contacts is interrupted.

Use the right language for control system programming

To communicate effectively in the English language, it's important to have the right vocabulary and know how to use that vocabulary effectively. To create effective industrial controls programs, it is important to have the right languages and know how to use those languages effectively. IEC 61131-3 provides the languages, and this article has provided guidance on effective use of LD



Refer below annexures for detailed specification and supplementary specifications.

Annexure 'A'

ASSEMBLY AND TESTING PROCEDURE FOR PLC MASTER PANEL

ASSEMBLY AND TESTING PROCEDURE FOR PLC SLAVE PANEL
(Driller's/Tool Pusher's/Muster)

* Data for the Annexure 'A' to be recorded as per SARA SAE/R&D-TP-0198-1

Annexure 'B'

SOFTWARE FUNCTION PROCEDURE FOR PLC MASTER PANEL

SOFTWARE FUNCTION PROCEDURE FOR PLC SLAVE PANEL
(Driller's/Tool Pusher's/Muster)

* Data for the Annexure 'B' to be recorded as per SARA SAE/R&D-TP-0198-2

Annexure 'E'

SOFTWARE/HARDWARE CODE REVIEW FOR PLC MASTER PANEL

SOFTWARE/HARDWARE CODE REVIEW FOR PLC SLAVE PANEL
(Driller's/Tool Pusher's/Muster)

* Data for the Annexure 'E' to be recorded as per SARA SAE/R&D-TP-0198-3

Annexure 'F'

MASTER SOFTWARE SECURITY REVIEW FOR PLC MASTER PANEL

MASTER SOFTWARE SECURITY REVIEW FOR PLC SLAVE PANEL
(Driller's/Tool Pusher's/Muster)

• Data for the Annexure 'F' to be recorded as per SARA SAE/R&D-TP-0198-4

Annexure 'H'

PLC PROGRAMME TRACEABILITY RECORD

* Data for the Annexure 'H' to be recorded as per SARA SAE/R&D-TP-0198-5



Annexure 'A'

ASSEMBLY AND TESTING PROCEDURE FOR PLC MASTER PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYING MAINS
POWER**

PANEL TYPE :

SALE ORDER NO:

CUSTOMER:

SERIAL NO MASTER PANEL:

ENCLOSURE SIZE:

UNIT NO/JOB NO:

DRAWING NO:

**** Before starting the work , Make sure drawing is latest**

S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC (i) CPU Input Voltage..... (ii) CPU Model.No..... (iii) Qty of Input & Output Module and Model No..... (iv) Qty of Output Module and Model No..... (iv) Qty of Analog Input Module and Model no						
2	Redundancy (i) Air Type (ii) Electrical Type						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
	(iii) Communication Type						
3	Timing						
	(i) PLC Power UP Timing						
	(ii) Software Response Time						
	(iii) Hot Standby Failover time (If Installed)						
	(iv) alarm activation delays						
4	Sequencing						
	(i) Yes/No						
5	Automation						
	(i) Yes/No						
6	Interlocks						
	(i) Electrical.....(Yes/No)						
	(ii) Air.....(Yes/No)						
7	Alarm Management						
	(i) Yes/No.....						
	(ii) Audible Sound.....(Yes/No)						
	(iii) Visual Sound.....(Yes/No)						
	(iv) Proper sound Produced.....(Yes/No)						
8	Error Management						
	(i) Pressure Gauge Reading.....(Ok/Not Ok)						
	(ii) PLC Error(Yes/No)						
	(iii) Communication Error.....(Yes/No)						
	(iv) Valve operation Error(Yes/No)						
	(v) Valve position Error.....(Yes/No)						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
9	Event Logging and historical archiving (i) Data Accurate.... (Yes/No)						
10	Initialization (i) PLC Power Up Time (ii) PLC Program Boot up time						
11	External Interface (i) Memory Card						
12	Operator Configuration Capabilities (i) Yes/No						
13	Mode of communication- (i) Modbus/Ethernet/Optical Fiber/ Wireless (ii) If Communication is Wireless, Modem S.No..... (iii) Modem encryption key.....						
14	Input & Output module wiring						
15	Output module wiring						
16	Mount Back plate W/O component on enclosure, check alignment, straightness & fitment on nuts and Bolts.						
17	Model No. Main Power Supply (SMPS) ---- I/P Voltage..... O/P Voltage.....						
18	Check tightness of Cooler or Fan bolt----- Serial Number.....						
19	X-Purge OR Y -Purge installed with a cover						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
	(bracket)						
20	Model No of X OR Y Purge----- Serial no of X OR Y Purge-----						
21	Flow Rate set at-----L/Min Purge Testing at.....PSI Purge Timing.....Min						
22	Relief vent Serial----- Number..... Tested at PSI.....						
23	Spark arrester installed and checked circlip is fixed over orifice Orifice Number-----						
24	Cooler air pressure setting done at -----Psi through regulator						
25	Power Gland used no ----qty Size-----						
26	Communication Gland no..... qty.....size						
27	Motor 1 Power Gland size..... Motor 2 Power Gland size.....						
28	Fluid level input supply Gland.....						
27	Gland for proximity size-----mm Qty.....nos						
28	Amplifiers set at NO/NC---- Number of amplifiers used.....						
29	Pilot light for Alarm Qty..... Colour.....						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
30	Push Button for lamp test..... Colour Number.....						
31	Push Button for Reset..... Colour..... Number.....						
32	Solenoid valves of 1/4 inch Qty.....						
33	Solenoid valves of 1/4 inch Qty----- a) Hold to operate (Batch No).....						
34	Battery connection done wih wire size of -----mm						
35	Serial number of all the transducers installed Manifold Transducers..... Annular Transducers..... Accumulator Trasnducers..... Rig Air Trasnducers..... Shear Acc Trasnducers..... Shear Reg Trasnducers.....						
36	Float switch connection done						
37	Main Input volt-----VAC, Freq-----Hz / Volt-----VDC						
38	Motor run and fluid level connections with safety barriers done at positions Serial Number-----for----- Serial Number-----for ----- Serial Number-----for ----- Serial Number-----for ----- Serial Number-----for ----- Serial Number-----for -----						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
	Serial Number-----for----- Serial Number-----for ----- Serial Number-----for----- Serial Number-----for-----						
39	Check tightness of battery terminals voltage----- AH---- Make-----						
40	Earthing for enclosure body done with a point left for customer end (Externally)						
41	Earthing at all the required points done , which include power supply (I/O module) ,SMPS,Cooler, and Earthing terminal Blocks (Green)						
42	Output Voltage from power supply has been adjusted to approx 26.5VDC (range 24VDC-28 VDC)						
43	Numbering of TB Is done in accordance with the drawings						
44	Interconnection for data communication between Master,Driller and Tool Pusher are according to drawing .						
45	Cable used for Power connection is of.....AWG						
46	Cable used for communication is of----- AWG						
47	All screw are tightened up with the help of lock washer						
48	The number on enclosures and door given by machine shop are matching.						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
49	Condition of enclosure i.e no dents scratch marks						
50	Fan and filter unit fixed neatly with fan in exhaust position						
51	Terminal Block used (Qty) a) Blue-----b) Yellow----- c) Gray----- d) Red----- e) Black-----f) Green----- Sensor/Actuator based Terminal Block(TB).....						
52	Electrical wiring connection of proximity wires: To be done with Blue terminal box---- Wiring Connection from TB to amplifiers to be done with blue wires.						
53	Horn applied Serial Number ----- wiring done at ----- Working tested OK						
54	Following tag applied before dispatch (tick if applied) Mains ----- Amplifiers I/P----- Communications----- Proximity name (IN/OUT)----- Earthing Stickers applied----- Names to solenoid valves----- Solenoid valves----- (Yes/No) Pressure Switch----- (Yes/No)						
	PLC Software testing with control system hardware						
55	Verify all Input/Output status of valve						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
56	Verify all alarms status						
57	Verify all Pressure reading status Vs. Pressure Transducer						

Workmanship rating-----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

Q C INSPECTOR (Sign/Date)



Annexure 'A'

ASSEMBLY AND TESTING PROCEDURE FOR PLC SLAVE PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYING MAINS
POWER**

PANEL TYPE :

SALE ORDER NO:

CUSTOMER:

SERIAL NO SLAVE PANEL:

ENCLOSURE SIZE:

UNIT NO/JOB NO:

DRAWING NO:

**** Before starting the work , Make sure drawing is latest**

S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC (i) CPU Input Voltage..... (ii) CPU Model.No..... (iii) Qty of Input & Output Module and Model No..... (iv) Qty of Output Module and Model No..... (iv) Qty of Analog Input Module and Model No..... (iv) Number of Analog Input Module (v) Qty of Analog Output Module and Model No.....						
2	Redundancy (iv) Air Type (v) Electrical Type						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	(vi) Communication Type						
3.	(c) Timing (i) PLC Power up Time (ii) Software Response Time (iii) Recovery time (iv) Hot Standby Failover time (If Installed) (v) alarm activation delays						
4	Sequencing (i) Yes/No						
5	Automation (i) Yes/No						
6	Interlocks (i) Electrical.....(Yes/No) (ii) Air.....(Yes/No)						
7	Alarm Management (i) Yes/No..... (ii) Audible Sound.....(Yes/No) (iii) Visual Sound.....(Yes/No) (iv) Proper sound Produced.....(Yes/No)						
8	Error Management (i) Pressure Gauge Reading.....(Ok/Not Ok) (ii) PLC Error(Yes/No) (iii) Communication Error.....(Yes/No) (iv) Valve oprtaion Error(Yes/No) (v) Valve position Error.....(Yes/No)						
9	Event Logging and historical						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	archiving (i) Data Accurate.... (Yes/No)						
10	Initialization (i) PLC Power Up Time (ii)PLC Program Boot up time						
11	External Interface (i)USB Port (ii)Memory Card (iii)Printer						
12	Operator Configuration Capabilities (i)Yes/No						
13	Mode of communication- (i) Modbus/Ethernet/Optical Fiber/ Wireless (ii) If Communication is Wireless, Modem Mod.No..... (iii) Modem encryption key.....						
14	Input module wiring						
15	Output module wiring						
16	Mount Back plate W/O component on enclosure, check alignment, straightness & fitment on nuts and Bolts.						
17	Mounting of CPU I/P and O/P on base plate. Power supply S.No:_____ CPU Module.No.:_____ Input /Output Module.No.----- _____						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	Output Module No-----						
18	Analog O/P Module.No._____						
19	Serial number of Main Power Supply (SMPS) --- I/P Voltage..... O/P Voltage.....						
20	Check tightness of Battery terminal..... voltage....VDC,-----AH.						
21	Power connecter Qty_____ Color_____						
22	Communication connector QTY..... Color.....						
23	Mains fail connection done at position _____.						
24	Terminal Block used (Qty) a) Blue-----b) Yellow----- c) Gray----- d) Red----- e) Black-----f) Green-----						
25	Push button with green light Indicator Qty _____ Nos.						
26	Push button with red light Indicator Qty _____ Nos.						
27	ON/OFF switch (Direction , Cap)						
28	Pilot light (alarm) Qty _____ Nos. Color						
29	Push button lamp test Number..... Color.....						
30	Pilot light (Communication, Error) Qty _____ Nos. Color_____						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
31	Pilot light (low rig air press.) Qty _____ Nos. Color _____						
32	Push button Acknowledge Number..... Color _____						
33	Pilot light (low hydraulic press.) Qty _____ Nos. Color _____						
34	Pilot light (mains fails) Qty _____ Nos. Color _____						
35	Pilot light (low fluid level) Qty _____ Nos. Color _____						
36	Pilot light (motor run) Qty _____ Nos Color _____						
37	Blind Cover Open /Closed properly(Yes/No) Shear Cover Open /Closed properly(Yes/No)						
38	Battery connection wire size---- mm						
39	Touch Screen Display S.No..... Model No..... Digital Pressure Gauge Model No..... (i) Accumulator Gauge S.No.... (ii) Annular Gauge S.No.... (iii) Manifold Gauge S.No.... (iv) Rig Air Gauge S.No..... (v) Shear ACC Gauge S.No..... (vi) Shear Reg Gauge S.No.....						
40	Verify Earthing at all the required points done						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	to include power supply (I/O Module), SMPS, Cooler, , and Earthing Terminal blocks (Green).						
41	Verify :- Earthing of Enclosure Body Provision of extra point for use by customer.						
42	Verify Numbering of TB is done in accordance with the drawing						
43	Output Voltage from Power supply has been adjusted to approx 26.5VDC (range 24VDC- 28 VDC)						
44	Cable used for input and output modules wiring is ofAWG Size of the wire used.....mm						
45	Serial No of Mini X- or Y Purge installed.....(if applied) Flow Rate set at-----L/Min Purge Testing at.....PSI						
46	Spark arrester installed and checked circlip is fixed over orifice Orifice Number-----						
47	Relief vent Serial.No.... Tested at PSI....						
48	All screw are tightened up with the help of Lock washer.						
49	The Number on enclosure and door given by machine shop are matching.						
50	The Fan and Filter unit (L&N) neatly with fan in Exhaust position						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
51	Condition of enclosures i.e no dents, scratch marks.						
52	Check tightness of cooler:Bolt----- Serial Number..... Cooler setting done at -----Psi through regulator						
53	Cooler setting done at -----Psi through regulator						
54	Gland for proximity size-----mm Qty.....nos						
55	Battery connection done wih wire size of -----mm						
56	Mains Fail connection done at position ----- accroding to drawings.						
57	Check tightness of battery terminals voltage---- AH---- Make-----						
58	Earthing for enclosure body done with a point left for customer end (Externally)						
59	Earthing at all the required points done , which include power supply (I/O module) ,SMPS,Cooler, and Earthing terminal Blocks (Green)						
60	Numbering of TB is done in accordance with the drawings						
61	Input/Output wires inside PVC Channels needs to be of accurate length and size and						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	also tied separately						
62	Interconnection for data communication connection between Master, Driller and Tool Pusher are according to drawing and communication is responding						
63	Size of the earthing wire Used-----						
64	All screw are tightened up with the help of lock washer						
65	The number on enclosures and door given by machine shop are matching.						
66	Condition of enclosure i.e no dents scratch marks						
67	Electrical wiring connection of proximity wires: To be done with Blue terminal box---- Wiring Connection from TB to amplifiers to be done with blue wires.						
68	Horn applied Serial Number ----- wiring done at ----- and -----						
69	Wires to be detailed for natural phase & earth also ----- before dispatch.						
70	Remove the identification Number/Marks before dispatch						
71	Following tag applied before dispatch(tick if applied) Mains-----(Yes/No) Amplifiers Input-----(Yes/No) Communications Gland-----(Yes/No)						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	Proximity name (IN/OUT)-----(Yes/No) Earthing Stickers applied-----(Yes/No) Total Tag applied-----(Yes/No)						
	PLC/HMI Software testing with control system hardware						
72	Verify all Input/Output status of valve						
73	Verify all alarms status						
74	Verify all Pressure reading status Vs. Pressure Transducer						

Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

QC INSPECTOR (Sign/Date)

Annexure 'A'



ASSEMBLY AND TESTING PROCEDURE FOR PLC SLAVE PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYING MAINS
POWER**

PANEL TYPE :

SALE ORDER NO:

CUSTOMER:

SERIAL NO SLAVE PANEL:

ENCLOSURE SIZE:

UNIT NO/JOB NO:

DRAWING NO:

**** Before starting the work , Make sure drawing is latest**

S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC (i) CPU Input Voltage..... (ii) CPU Model.No..... (iii) Qty of Input & Output Module and Model No..... (iv) Qty of Output Module and Model No..... (iv) Qty of Analog Input Module and Model No..... (v) Number of Analog Input Module (v) Qty of Analog Output Module and Model No.....						
2	Redundancy (vii) Air Type (viii) Electrical Type (ix) Communication Type						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
3.	(c) Timing (i) PLC Power up Time (ii) Software Response Time (iii) Recovery time (iv) Hot Standby Failover time (If Installed) (v) alarm activation delays						
4	Sequencing (i) Yes/No						
5	Automation (i) Yes/No						
6	Interlocks (i) Electrical.....(Yes/No) (ii) Air.....(Yes/No)						
7	Alarm Management (i) Yes/No..... (ii) Audible Sound.....(Yes/No) (iii) Visual Sound.....(Yes/No) (iv) Proper sound Produced.....(Yes/No)						
8	Error Management (i) Pressure Gauge Reading.....(Ok/Not Ok) (ii) PLC Error(Yes/No) (iii) Communication Error.....(Yes/No) (iv) Valve oprtaion Error(Yes/No) (v) Valve position Error.....(Yes/No)						
9	Event Logging and historical archiving (i) Data Accurate.... (Yes/No)						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
10	Initialization (i) PLC Power Up Time (ii) PLC Program Boot up time						
11	External Interface (i) USB Port (ii) Memory Card (iii) Printer						
12	Operator Configuration Capabilities (i) Yes/No						
13	Mode of communication- (i) Modbus/Ethernet/Optical Fiber/ Wireless (ii) If Communication is Wireless, Modem Mod.No..... (iii) Modem encryption key.....						
14	Input module wiring						
15	Output module wiring						
16	Mount Back plate W/O component on enclosure, check alignment, straightness & fitment on nuts and Bolts.						
17	Mounting of CPU I/P and O/P on base plate. Power supply S.No: _____ CPU Module No.: _____ Input Module No. _____ Output Module No. _____						
18	Analog O/P Module No. _____						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
19	Serial number of Main Power Supply (SMPS) ---- I/P Voltage..... O/P Voltage.....						
20	Check tightness of Battery terminal.... voltage....VDC,-----AH.						
21	Power connecter Qty _____ Color _____						
22	Communication connector QTY..... Color.....						
23	Mains fail connection done at position _____.						
24	Terminal Block used (Qty) a) Blue-----b) Yellow----- c) Gray----- d) Red----- e) Black-----f) Green-----						
25	Push button with green light Indicator Qty _____ Nos.						
26	Push button with red light Indicator Qty _____ Nos.						
27	ON/OFF switch (Direction , Cap)						
28	Pilot light (alarm) Qty _____ Nos. Color _____						
29	Push button lamp test Number..... Color.....						
30	Pilot light (Communication, Error) Qty _____ Nos. Color _____						
31	Pilot light (low rig air press.) Qty _____ Nos. Color _____						
32	Push button Acknowledge Number.....						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	Color _____						
33	Pilot light (low hydraulic press.) Qty _____ Nos. Color _____						
34	Pilot light (mains fails) Qty _____ Nos. Color _____						
35	Pilot light (low fluid level) Qty _____ Nos. Color _____						
36	Pilot light (motor run) Qty _____ Nos Color _____						
37	Blind Cover Open /Closed properly(Yes/No) Shear Cover Open /Closed properly(Yes/No)						
38	Battery connection wire size---- mm						
39	Touch Screen DisplayS.No..... Model No..... Digital Pressure Gauge Model No..... (i) Accumulator Gauge S.No..... (ii) Annular Gauge S.No..... (iii) Manifold Gauge S.No.... (iv) Rig Air Gauge S.No..... (v) Shear ACC Gauge S.No..... (vi) Shear Reg Gauge						
40	Verify Earthing at all the required points done to include power supply (I/O Module), SMPS, Cooler, , and Earthing Terminal blocks (Green).						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
41	Verify :- Earthing of Enclosure Body Provision of extra point for use by customer.						
42	Verify Numbering of TB is done in accordance with the drawing						
43	Output Voltage from Power supply has been adjusted to approx 26.5VDC (range 24VDC-28 VDC)						
44	Cable used for input and output modules wiring is ofAWG Size of the wire used.....mm						
45	Serial No of Mini X- or Y Purge installed.....(if applied) Flow Rate set at-----L/Min Purge Testing at.....PSI						
46	Spark arrester installed and checked circlip is fixed over orifice Orifice Number-----						
47	Relief vent Serial.No.... Tested at PSI....						
48	All screw are tightened up with the help of Lock washer.						
49	The Number on enclosure and door given by machine shop are matching.						
50	The Fan and Filter unit (L&N) neatly with fan in Exhaust posistion						
51	Condition of enclosures i.e no dents, scratch marks.						
52	Check tightness of cooler:Bolt----- Serial Number.....						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	Cooler setting done at -----Psi through regulator						
53	Cooler setting done at -----Psi through regulator						
54	Gland for proximity size-----mm Qty.....nos						
55	Battery connection done wih wire size of ----mm						
56	Mains Fail connection done at position ----- accroding to drawings.						
57	Check tightness of battery terminals voltage----AH---- Make-----						
58	Earthing for enclosure body done with a point left for customer end (Externally)						
59	Earthing at all the required points done , which include power supply (I/O module) ,SMPS,Cooler, and Earthing terminal Blocks (Green)						
60	Numbering of TB is done in accordance with the drawings						
61	Input/Output wires inside PVC Channels needs to be of accurate length and size and also tied separtely						
62	Interconnection for data communication connection between Master,Driller and Tool Pusher are according to drawing and						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	communication is responding						
63	Size of the earthing wire Used-----						
64	All screw are tightened up with the help of lock washer						
65	The number on enclosures and door given by machine shop are matching.						
66	Condition of enclosure i.e no dents scratch marks						
67	Electrical wiring connection of proximity wires: To be done with Blue terminal box---- Wiring Connection from TB to amplifiers to be done with blue wires.						
68	Horn applied Serial Number ----- wiring done at ----- and -----						
69	Wires to be detailed for natural phase & earth also -----before dispatch.						
70	Remove the identification Number/Marks before dispatch						
71	Following tag applied before dispatch(tick if applied) Mains-----(Yes/No) Amplifiers Input-----(Yes/No) Communications Gland-----(Yes/No) Proximity name (IN/OUT)-----(Yes/No) Earthing Stickers applied-----(Yes/No) Total Tag applied-----(Yes/No)						
	PLC/HMI Software testing with control						



S.No	System	Practical Value/status	Status	Remark (If any)	Date	Done By	Checked By
	system hardware						
72	Verify all Input/Output status of valve						
73	Verify all alarms status						
74	Verify all Pressure reading status Vs. Pressure Transducer						

Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

QC INSPECTOR (Sign/Date)



Annexure 'B'

SOFTWARE FUNCTION PROCEDURE FOR PLC MASTER PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYING MAINS
POWER**

PANEL TYPE :

ENCLOSURE SIZE:

SALE ORDER NO:

UNIT NO/JOB NO:

CUSTOMER:

DRAWING NO:

SERIAL NO MASTER PANEL:

**** Before starting the work , Make sure drawing is latest**

S.No	System	Practical Value	Status	Remark (If any)	Date	Done By	Checked By
1	PLC Basic Feature (i) CPU Model Number..... (ii) Type of Programming..... (iii) Floating Point(real) data function.....(Yes/No) (iv) Non-Volatile flash memory for Program Storage (v) Battery Backup for program,RTC.....(Yes/No) (vi) Run/Stop Switch.....(Yes/No) (vii) Number of RS232 Port..... Number of RS-485 Port..... (viii) Carrier Style.....						
2	Mode of communication- Modbus/Ethernet/Optical Fiber/ Wireless Communication						



S.No	System	Practical Value	Status	Remark (If any)	Date	Done By	Checked By
	(i) Ethernet Restart Push Button....(Yes/No) (ii) Ethernet Data transmission.....						
3	PLC Operational Timing (i) PLC Power Up Time (ii) Software Response Time (iii) Recovery time (iv) Hot Standby Failover time (If Installed) (v) alarm activation delays						
4	PLC CPU Input/Output/Analog module/ LED Status (i) RUN/STOP (ii) MAINT (iii) ERROR						
5	PLC Operation timing (i) All control valve operation performed properly..... (ii) All alarm operaton performed properly..... (iii) One Control Valve Executiuon Time						
6	PLC Alarm Timing (i) Communication Error (ii) Low Fluid Level (iii) Low Accumulator Pressure (iv) Blind/Shear Cover Open (v) Mains Fail (vi) Alarm when operation is not performed.....(Yes/No).....Time						
	PLC/HMI Software testing with control system hardware						
7	Verify all Input/Output status of valve						
8	Verify all alarms status						
9	Verify all Pressure reading status Vs. Pressure Transduseer						



Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

QC INSPECTOR (Sign/Date)



Annexure 'B'

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYING MAINS
POWER**

PANEL TYPE :

SALE ORDER NO:

CUSTOMER:

SERIAL NO SLAVE PANEL:

ENCLOSURE SIZE:

UNIT NO/JOB NO:

DRAWING NO.:

** Before starting the work , Make sure drawing is latest

S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC Basic Feature <ul style="list-style-type: none"> (i) CPU Model Number..... (ii) Type of Programming..... (iii) Floating Point(real) data function.....(Yes/No) (iv) Non-Volatile flash memory for Program Storage (v) Battery Backup for program,RTC.....(Yes/No) (vi) Run/Stop Switch.....(Yes/No) (vii) Number of RS232..... Number of RS-485 Communication----- (viii) Carrier Style..... 						
2	Mode of communication- Modbus/Ethernet/Optical Fiber/ Wireless <ul style="list-style-type: none"> (i) Ethernet Restart Push Button....(Yes/No) (ii) Ethernet Data transmission..... 						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
3	Timing <ul style="list-style-type: none"> (i) PLC Power Up Time (ii) Software Response Time (iii) Recovery time (iv) Hot Standby Failover time (If Installed) (v) alarm activation delays 						
4	PLC CPU Input/Output/Analog module/ LED Status <ul style="list-style-type: none"> (i) RUN/STOP (ii) MAINT (iii) ERROR 						
5	PLC Operation timing <ul style="list-style-type: none"> (i) All control valve operation performed properly..... (ii) All alarm operaton performed Properly..... (iii) One Control Valve Executuion Time..... 						
6	PLC Alarm Timing <ul style="list-style-type: none"> (i) Communication Error (ii) Low Fluid Level (iii) Low Accumulator Pressure (iv) Blind/Shear Cover Open (v) Mains Fail (vi) Operation fail Alarm(Yes/No) 						
7	HMI Basic Feature <ul style="list-style-type: none"> (i) Display Size (ii) Operating System 						
8	HMI Timing <ul style="list-style-type: none"> (i) Hmi boot up timing 						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
	PLC/HMI Software testing with control system hardware						
9	Verify all Input/Output status of valve						
10	Verify all alarms status						
11	Verify all Pressure reading status Vs. Pressure Transducer						

Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

C If not then

Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

Q C INSPECTOR (Sign/Date)



Annexure 'B'
SOFTWARE FUNCTION PROCEDURE FOR PLC SLAVE PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYING MAINS
POWER**

PANEL TYPE :

ENCLOSURE SIZE:

SALE ORDER NO: UNIT NO/JOB NO:

CUSTOMER: DRAWING NO:

SERIAL NO SLAVE PANEL:

**** Before starting the work , Make sure drawing is latest**

S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC Basic Feature (i) CPU Model Number..... (ii) Type of Programming..... (iii) Floating Point(real) data function.....(Yes/No) (iv) Non-Volatile flash memory for Program Storage (v) Battery Backup for program,RTC.....(Yes/No) (vi) Run/Stop Switch.....(Yes/No) (vii) Number of RS232..... Number of RS-485 Communication----- (viii) Carrier Style.....						
2	Mode of communication- Modbus/Ethernet/Optical Fiber/ Wireless (i) Ethernet Restart Push Button....(Yes/No) (ii) Ethernet Data transmission....						
3	Timing						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
	(i) PLC Power Up Time (ii) Software Response Time (iii) Recovery time (iv) Hot Standby Failover time (If Installed) (v) alarm activation delays						
4	PLC CPU Input/Output/Analog module/ LED Status (i) RUN/STOP (ii) MAINT (iii) ERROR						
5	PLC Operation timing (i) All control valve operation performed properly..... (ii) All alarm operaton performed Properly..... (iii) One Control Valve Executiuon Time.....						
6	PLC Alarm Timing (i) Communication Error (ii)Low Fluid Level (iii)Low Accumulator Pressure (iv)Blind/Shear Cover Open (v)Mains Fail (vi) Operation fail Alarm(Yes/No)						
7	HMI Basic Feature (i) Display Size (ii) Operating System						
8	HMI Timing (i) Hmi boot up timing						
	PLC/HMI Software testing with control system						



S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
	hardware						
9	Verify all Input/Output status of valve						
10	Verify all alarms status						
11	Verify all Pressure reading status Vs. Pressure Transducer						

Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

C

If not then

Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

QC INSPECTOR (Sign/Date)

C



Annexure 'E'

SOFTWARE/HARDWARE CODE REVIEW FOR PLC MASTER PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYIN MAINS
POWER**

PANEL TYPE :

ENCLOSURE SIZE:

SALE ORDER NO:

UNIT NO/JOB NO:

CUSTOMER:

DRAWING NO:

SERIAL NO MASTER PANEL:

**** Before starting the work , Make sure drawing is latest**

Pressure Switch No	Plc input	Plc Input addressing	Terminal Block No		Solenoid No	Plc output No	PLC Output addressing
PS1	I0.0	ANNULAR OPEN	TB1-1	SOL-1A	Q0.0	ANNULAR OPEN	TB2-1
PS2	I0.1	ANNULAR CLOSE	TB1-2	SOL-1B	Q0.1	ANNULAR CLOSE	TB2-2
PS3	I0.2	UPPER PIPE OPEN	TB1-3	SOL-2A	Q0.2	UPPER PIPE OPEN	TB2-3
PS4	I0.3	UPPER PIPE CLOSE	TB1-4	SOL-2B	Q0.3	UPPER PIPE CLOSE	TB2-4
PS5	I0.4	BLIND/SHEAR RAM OPEN	TB1-5	SOL-3A	Q0.4	BLIND/SHEAR RAM OPEN	TB2-5
PS6	I0.5	BLIND/SHEAR RAM CLOSE	TB1-6	SOL-3B	Q0.5	BLIND/SHEAR RAM CLOSE	TB2-6
PS7	I0.6	MIDDLE PIPE OPEN	TB1-7	SOL-4A	Q0.6	MIDDLE PIPE OPEN	TB2-7
PS8	I0.7	MIDDLE PIPE CLOSE	TB1-8	SOL-4B	Q0.7	MIDDLE PIPE CLOSE	TB2-8
PS9	I1.0	LOWER PIPE OPEN	TB1-9	SOL-5A	Q1.0	LOWER PIPE OPEN	TB2-9
PS10	I1.1	LOWER PIPE CLOSE	TB1-10	SOL-5B	Q1.1	LOWER PIPE CLOSE	TB2-10
PS11	I1.2	UPPER CHOKE OPEN	TB1-11	SOL-6A	Q2.0	UPPER CHOKE OPEN	TB2-11
PS12	I1.3	UPPER CHOKE CLOSE	TB1-12	SOL-6B	Q2.1	UPPER CHOKE CLOSE	TB2-12
PS13	I1.4	UPPER KILL OPEN	TB1-13	SOL-7A	Q2.2	UPPER KILL OPEN	TB2-13
PS14	I1.5	UPPER KILL CLOSE	TB1-14	SOL-7B	Q2.3	UPPER KILL CLOSE	TB2-14
PS15	I2.0	LOWER CHOKE OPEN	TB1-15	SOL-8A	Q2.4	LOWER CHOKE OPEN	TB2-15
PS16	I2.1	LOWER CHOKE CLOSE	TB1-16	SOL-8B	Q2.5	LOWER CHOKE CLOSE	TB2-16
PS17	I2.2	LOWER KILL OPEN	TB1-17	SOL-9A	Q2.6	LOWER KILL OPEN	TB2-17
PS18	I2.3	LOWER KILL CLOSE	TB1-18	SOL-9B	Q2.7	LOWER KILL CLOSE	TB2-18
PS19	I2.4	SPARE 1 OPEN	TB1-19	SOL-10A	Q3.0	SPARE 1 OPEN	TB2-19
PS20	I2.5	SPARE 1 CLOSE	TB1-20	SOL-10B	Q3.1	SPARE 1 CLOSE	TB2-20
PS21	I2.6	SPARE 2 OPEN	TB1-21	SOL-11A	Q3.2	SPARE 2 OPEN	TB2-21



Pressure Switch No	Plc input	Plc Input addressing	Terminal Block No		Solenoid No	Plc output No	PLC Output addressing
PS22	I2.7	SPARE 2 CLOSE	TB1-22	SOL-11B	Q3.3	SPARE 2 CLOSE	TB2-22
PS23	I3.0	SPARE 3 OPEN	TB1-23	SOL-12A	Q3.4	SPARE 3 OPEN	TB2-23
PS24	I3.1	SPARE 3 CLOSE	TB1-24	SOL-12B	Q3.5	SPARE 3 CLOSE	TB2-24
PS25	I3.2	MANIFOLD BYPASS LOW	TB1-25	SOL-13A	Q3.6	BYPASS LOW	TB2-25
PS26	I3.3	MANIFOLD BYPASS HIGH	TB1-26	SOL-13B	Q3.7	BYPASS HIGH	TB2-26
PS27	I3.4	SHEAR BYPASS LOW	TB1-27	SOL-14A	Q4.0	SHEAR BYPASS LOW	TB2-27
PS28	I3.5	SHEAR BYPASS HIGH	TB1-28	SOL-14B	Q4.1	SHEAR BYPASS HIGH	TB2-28
PS29	I3.6		TB1-29	SOL-15A	Q4.2	ANN REG INC	TB2-29
PS30	I3.7		TB1-30	SOL-15B	Q4.3	ANN REG DEC	TB2-30
PS31	I4.0		TB1-31	SOL-16A	Q4.4	MANI REG INC	TB2-31
PS32	I4.1		TB1-32	SOL-16B	Q4.5	MANI REG DEC	TB2-32
PS33	I4.2		TB1-33	SOL-17A	Q4.6		TB2-33
CONTACT 3	I4.3	LOW FLUID LEVEL	TB1-34	SOL-17B	Q4.7		TB2-34
CONTACT 4	I4.4	BLIND/SHEAR COVER OPEN ALARM SENSOR	TB1-35	SOL-18A	Q5.0		TB2-35
CONTACT 5	I4.5	MAINS FAIL	TB1-36	SOL-18B	Q5.1		TB2-36
CONTACT 6	I4.6	PURGE FAIL	TB1-37	SOL-19A	Q5.2		TB2-37
CONTACT 7	I4.7	PUMP 1 FAULT	TB1-38	SVH	Q5.3	HOLD TO OPERATE	TB2-38
CONTACT 8	I5.0	PUMP 1 POWER FAIL	TB1-39	LIGHT	Q5.4	LOW ACC PR ALARM	TB2-39
CONTACT 9	I5.1	PUMP 1 RUN	TB1-40	LIGHT	Q5.5	LOW MANIFOLD PR ALARM	TB2-40
CONTACT 10	I5.2	PUMP 2 FAULT	TB1-41	LIGHT	Q5.6	LOW RIG AIR PR ALARM	TB2-41
CONTACT 11	I5.3	PUMP 2 POWER FAIL	TB1-42	LIGHT	Q5.7	LOW SHEAR BYPASS PR ALARM	TB2-42
CONTACT 12	I5.4	PUMP 2 RUN	TB1-43	LIGHT	Q6.0	LOW FLUID LEVEL	TB2-43
CONTACT 13	I5.5	ALARM AK	TB1-44	LIGHT	Q6.1	BLIND/SHEAR COVER OPEN ALARM	TB2-44
CONTACT 14	I5.6	LAMP TEST	TB1-45	LIGHT	Q6.2	MAINS FAIL	TB2-45
				LIGHT	Q6.3	PURGE FAIL	TB2-46
				LIGHT	Q6.4	COMMUNICATION FAIL ALARM	TB2-47
				LIGHT	Q6.5	PUMP 1 FAULT	TB2-48
				LIGHT	Q6.6	PUMP 1 POWER FAIL	TB2-49
				LIGHT	Q6.7	PUMP 1 RUN	TB2-50
PT1	A10.0	TRANSDUSER ACCU PRESSURE	TB3-1	LIGHT	Q7.0	PUMP 2 FAULT	TB2-51
PT2	A10.1	TRANSDUSER MANIFOLD PRESSURE	TB3-2	LIGHT	Q7.1	PUMP 2 POWER FAIL	TB2-52
PT3	A10.2	TRANSDUSER ANNU PRESSURE	TB3-3	LIGHT	Q7.2	PUMP 2 RUN	TB2-53
PT4	A10.3	TRANSDUSER SHEAR BYPASS PRESSURE	TB3-4	LIGHT	Q7.3	ALARM SOUNDER	TB2-54
PT5	A10.4	TRANSDUSER AIR PRESSURE	TB3-5	LIGHT	Q7.4	BECON LIGHT	TB2-55

Workmanship rating----



/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

Q C INSPECTOR (Sign/Date)



Annexure 'E'

SOFTWARE/HARDWARE CODE REVIEW FOR PLC SLAVE PANEL

MODEL NO: PLC-SL1-SS-G-0-2-14-0-Y-0-WE

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYIN MAINS
POWER**

PANEL TYPE : PLC

SALE ORDER NO: SO/110/2425/0250

CUSTOMER: GREATWALL

SERIAL NO SLAVE PANEL:D-1493-01-4224

ENCLOSURE SIZE:36"X36"X12"

UNIT NO/JOB NO:01-4224/610498-1

DRAWING NO:SKE-0970-3

**** Before starting the work , Make sure drawing is latest**

Pressure Switch No	Plc input	REMOTE INPUT	Terminal Block No	Solenoid No	Plc output No	PLC Output	Terminal Block No
CONTACT1	I0.0	ANNUAL OPEN	TB1-1	LIGHT	Q0.0	ANNUAL OPEN	TB2-1
CONTACT2	I0.1	ANNUAL CLOSE	TB1-2	LIGHT	Q0.1	ANNUAL CLOSE	TB2-2
CONTACT3	I0.2	UPPER PIPE OPEN	TB1-3	LIGHT	Q0.2	UPPER PIPE OPEN	TB2-3
CONTACT4	I0.3	UPPER PIPE CLOSE	TB1-4	LIGHT	Q0.3	UPPER PIPE CLOSE	TB2-4
CONTACT5	I0.4	BLIND/SHEAR RAM OPEN	TB1-5	LIGHT	Q0.4	BLIND/SHEAR RAM OPEN	TB2-5
CONTACT6	I0.5	BLIND/SHEAR RAM CLOSE	TB1-6	LIGHT	Q0.5	BLIND/SHEAR RAM CLOSE	TB2-6
CONTACT7	I0.6	MIDDLE PIPE OPEN	TB1-7	LIGHT	Q0.6	MIDDLE PIPE OPEN	TB2-7
CONTACT8	I0.7	MIDDLE PIPE CLOSE	TB1-8	LIGHT	Q0.7	MIDDLE PIPE CLOSE	TB2-8
CONTACT9	I1.0	LOWER PIPE OPEN	TB1-9	LIGHT	Q1.0	LOWER PIPE OPEN	TB2-9
CONTACT10	I1.1	LOWER PIPE CLOSE	TB1-10	LIGHT	Q1.1	LOWER PIPE CLOSE	TB2-10
CONTACT11	I1.2	UPPER CHOKE OPEN	TB1-11	LIGHT	Q2.0	UPPER CHOKE OPEN	TB2-11
CONTACT12	I1.3	UPPER CHOKE CLOSE	TB1-12	LIGHT	Q2.1	UPPER CHOKE CLOSE	TB2-12
CONTACT13	I1.4	UPPER KILL OPEN	TB1-13	LIGHT	Q2.2	UPPER KILL OPEN	TB2-13
CONTACT14	I1.5	UPPER KILL CLOSE	TB1-14	LIGHT	Q2.3	UPPER KILL CLOSE	TB2-14
CONTACT15	I2.0	LOWER CHOKE OPEN	TB1-15	LIGHT	Q2.4	LOWER CHOKE OPEN	TB2-15
CONTACT16	I2.1	LOWER CHOKE CLOSE	TB1-16	LIGHT	Q2.5	LOWER CHOKE CLOSE	TB2-16
CONTACT17	I2.2	LOWER KILL OPEN	TB1-17	LIGHT	Q2.6	LOWER KILL OPEN	TB2-17
CONTACT18	I2.3	LOWER KILL CLOSE	TB1-18	LIGHT	Q2.7	LOWER KILL CLOSE	TB2-18
CONTACT19	I2.4	SPARE 1 OPEN	TB1-19	LIGHT	Q3.0	SPARE 1 OPEN	TB2-19
CONTACT20	I2.5	SPARE 1 CLOSE	TB1-20	LIGHT	Q3.1	SPARE 1 CLOSE	TB2-20
CONTACT21	I2.6	SPARE 2 OPEN	TB1-21	LIGHT	Q3.2	SPARE 2 OPEN	TB2-21



Pressure Switch No	Plc input	REMOTE INPUT	Terminal Block No	Solenoid No	Plc output No	PLC Output	Terminal Block No
CONTACT22	I2.7	SPARE 2 CLOSE	TB1-22	LIGHT	Q3.3	SPARE 2 CLOSE	TB2-22
CONTACT23	I3.0	SPARE 3 OPEN	TB1-23	LIGHT	Q3.4	SPARE 3 OPEN	TB2-23
CONTACT24	I3.1	SPARE 3 CLOSE	TB1-24	LIGHT	Q3.5	SPARE 3 CLOSE	TB2-24
CONTACT25	I3.2	BYPASS LOW	TB1-25	LIGHT	Q3.6	BYPASS LOW	TB2-25
CONTACT26	I3.3	BYPASS HIGH	TB1-26	LIGHT	Q3.7	BYPASS HIGH	TB2-26
CONTACT27	I3.4	SHEAR BYPASS LOW	TB1-27	LIGHT	Q4.0	SHEAR BYPASS LOW	TB2-27
CONTACT28	I3.5	SHEAR BYPASS HIGH	TB1-28	LIGHT	Q4.1	SHEAR BYPASS HIGH	TB2-28
CONTACT29	I3.6	ANN REG INC	TB1-29	LIGHT	Q4.2		TB2-29
CONTACT30	I3.7	ANN REG DEC	TB1-30	LIGHT	Q4.3		TB2-30
CONTACT31	I4.0	MANI REG INC	TB1-31	LIGHT	Q4.4		TB2-31
CONTACT32	I4.1	MANI REG DEC	TB1-32	LIGHT	Q4.5		TB2-32
CONTACT33	I4.2		TB1-33	LIGHT	Q4.6	LOW ACC PR ALARM	TB2-33
CONTACT34	I4.3		TB1-34	LIGHT	Q4.7	LOW MANIFOLD PR ALARM	TB2-34
CONTACT35	I4.4		TB1-35	LIGHT	Q5.0	LOW RIG AIR PR ALARM	TB2-35
CONTACT36	I4.5		TB1-36	LIGHT	Q5.1	LOW SHEAR BYPASS PR ALARM	TB2-36
CONTACT37	I4.6		TB1-37	LIGHT	Q5.2	LOW FLUID LEVEL	TB2-37
CONTACT38	I4.7	ALARM AK	TB1-38	LIGHT	Q5.3	BLIND/SHEAR COVER OPEN ALARM	TB2-38
CONTACT39	I5.0	LAMP TEST	TB1-39	LIGHT	Q5.4	MAINS FAIL	TB2-39
CONTACT40	I5.1	BLIND/SHEAR COVER OPEN SENSOR	TB1-40	LIGHT	Q5.5	PURGE FAIL	TB2-40
CONTACT41	I5.2	PURGE FAIL	TB1-41	LIGHT	Q5.6	COMMUNICATION FAIL ALARM	TB2-41
CONTACT42	I5.3	MUD PUMP 1 PULS INPUT	TB1-42	LIGHT	Q5.7	PUMP 1 FAULT	TB2-42
CONTACT43	I5.4	MUD PUMP 2 PULS INPUT	TB1-43	LIGHT	Q6.0	PUMP 1 POWER FAIL	TB2-43
CONTACT44	I5.5	MUD PUMP 3 PULS INPUT	TB1-44	LIGHT	Q6.1	PUMP 1 RUN	TB2-44
				LIGHT	Q6.2	PUMP 2 FAULT	TB2-45
PT11	AITR1	CHOKE PRESSURE 1, 20K		LIGHT	Q6.3	PUMP 2 POWER FAIL	TB2-46
PT12	AITR2	CHOKE PRESSURE 2, 20K		LIGHT	Q6.4	PUMP 2 RUN	TB2-47
PT13	AITR3	DRILL PIPE PRESSURE 20K		SOUNDER	Q6.5	ALARM SOUNDER	TB2-48
PT14	AITR4	CASEING PRESSURE 20K		LIGHT	Q6.6	BECON LIGHT	TB2-49
POS1	POS1	POSITION SENSOR 1					
POS2	POS2	POSITION SENSOR 2					
				GAUGE		GAUGE ACCU PRESSURE	TB3-1
				GAUGE		GAUGE MANIFOLD PRESSURE	TB3-2
				GAUGE		GAUGE ANN PRESSURE	TB3-3
				GAUGE		GAUGE AIR PRESSURE	TB3-4
				GAUGE		GAUGE SHEAR BYPASS PRESSURE	TB3-5



Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

QC INSPECTOR (Sign/Date)



Annexure 'E'

SOFTWARE/HARDWARE CODE REVIEW FOR PLC SLAVE PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYIN MAINS
POWER**

PANEL TYPE :

ENCLOSURE SIZE:

SALE ORDER NO:

UNIT NO/JOB NO:

CUSTOMER:

DRAWING NO:

SERIAL NO SLAVE PANEL:

**** Before starting the work , Make sure drawing is latest**

Pressure Switch No	Plc input	REMOTE INPUT	Terminal Block No	Solenoid No	Plc output No	PLC Output	Terminal Block No
CONTACT1	I0.0	ANNULAR OPEN	TB1-1	LIGHT	Q0.0	ANNULAR OPEN	TB2-1
CONTACT2	I0.1	ANNULAR CLOSE	TB1-2	LIGHT	Q0.1	ANNULAR CLOSE	TB2-2
CONTACT3	I0.2	UPPER PIPE OPEN	TB1-3	LIGHT	Q0.2	UPPER PIPE OPEN	TB2-3
CONTACT4	I0.3	UPPER PIPE CLOSE	TB1-4	LIGHT	Q0.3	UPPER PIPE CLOSE	TB2-4
CONTACT5	I0.4	BLIND/SHEAR RAM OPEN	TB1-5	LIGHT	Q0.4	BLIND/SHEAR RAM OPEN	TB2-5
CONTACT6	I0.5	BLIND/SHEAR RAM CLOSE	TB1-6	LIGHT	Q0.5	BLIND/SHEAR RAM CLOSE	TB2-6
CONTACT7	I0.6	MIDDLE PIPE OPEN	TB1-7	LIGHT	Q0.6	MIDDLE PIPE OPEN	TB2-7
CONTACT8	I0.7	MIDDLE PIPE CLOSE	TB1-8	LIGHT	Q0.7	MIDDLE PIPE CLOSE	TB2-8
CONTACT9	I1.0	LOWER PIPE OPEN	TB1-9	LIGHT	Q1.0	LOWER PIPE OPEN	TB2-9
CONTACT10	I1.1	LOWER PIPE CLOSE	TB1-10	LIGHT	Q1.1	LOWER PIPE CLOSE	TB2-10
CONTACT11	I1.2	UPPER CHOKE OPEN	TB1-11	LIGHT	Q2.0	UPPER CHOKE OPEN	TB2-11
CONTACT12	I1.3	UPPER CHOKE CLOSE	TB1-12	LIGHT	Q2.1	UPPER CHOKE CLOSE	TB2-12
CONTACT13	I1.4	UPPER KILL OPEN	TB1-13	LIGHT	Q2.2	UPPER KILL OPEN	TB2-13
CONTACT14	I1.5	UPPER KILL CLOSE	TB1-14	LIGHT	Q2.3	UPPER KILL CLOSE	TB2-14
CONTACT15	I2.0	LOWER CHOKE OPEN	TB1-15	LIGHT	Q2.4	LOWER CHOKE OPEN	TB2-15
CONTACT16	I2.1	LOWER CHOKE CLOSE	TB1-16	LIGHT	Q2.5	LOWER CHOKE CLOSE	TB2-16
CONTACT17	I2.2	LOWER KILL OPEN	TB1-17	LIGHT	Q2.6	LOWER KILL OPEN	TB2-17
CONTACT18	I2.3	LOWER KILL CLOSE	TB1-18	LIGHT	Q2.7	LOWER KILL CLOSE	TB2-18
CONTACT19	I2.4	SPARE 1 OPEN	TB1-19	LIGHT	Q3.0	SPARE 1 OPEN	TB2-19
CONTACT20	I2.5	SPARE 1 CLOSE	TB1-20	LIGHT	Q3.1	SPARE 1 CLOSE	TB2-20
CONTACT21	I2.6	SPARE 2 OPEN	TB1-21	LIGHT	Q3.2	SPARE 2 OPEN	TB2-21
CONTACT22	I2.7	SPARE 2 CLOSE	TB1-22	LIGHT	Q3.3	SPARE 2 CLOSE	TB2-22



Pressure Switch No	Plc input	REMOTE INPUT	Terminal Block No	Solenoid No	Plc output No	PLC Output	Terminal Block No
CONTACT23	I3.0	SPARE 3 OPEN	TB1-23	LIGHT	Q3.4	SPARE 3 OPEN	TB2-23
CONTACT24	I3.1	SPARE 3 CLOSE	TB1-24	LIGHT	Q3.5	SPARE 3 CLOSE	TB2-24
CONTACT25	I3.2	BYPASS LOW	TB1-25	LIGHT	Q3.6	BYPASS LOW	TB2-25
CONTACT26	I3.3	BYPASS HIGH	TB1-26	LIGHT	Q3.7	BYPASS HIGH	TB2-26
CONTACT27	I3.4	SHEAR BYPASS LOW	TB1-27	LIGHT	Q4.0	SHEAR BYPASS LOW	TB2-27
CONTACT28	I3.5	SHEAR BYPASS HIGH	TB1-28	LIGHT	Q4.1	SHEAR BYPASS HIGH	TB2-28
CONTACT29	I3.6	ANN REG INC	TB1-29	LIGHT	Q4.2		TB2-29
CONTACT30	I3.7	ANN REG DEC	TB1-30	LIGHT	Q4.3		TB2-30
CONTACT31	I4.0	MANI REG INC	TB1-31	LIGHT	Q4.4		TB2-31
CONTACT32	I4.1	MANI REG DEC	TB1-32	LIGHT	Q4.5		TB2-32
CONTACT33	I4.2		TB1-33	LIGHT	Q4.6	LOW ACC PR ALARM	TB2-33
CONTACT34	I4.3		TB1-34	LIGHT	Q4.7	LOW MANIFOLD PR ALARM	TB2-34
CONTACT35	I4.4		TB1-35	LIGHT	Q5.0	LOW RIG AIR PR ALARM	TB2-35
CONTACT36	I4.5		TB1-36	LIGHT	Q5.1	LOW SHEAR BYPASS PR ALARM	TB2-36
CONTACT37	I4.6		TB1-37	LIGHT	Q5.2	LOW FLUID LEVEL	TB2-37
CONTACT38	I4.7	ALARM AK	TB1-38	LIGHT	Q5.3	BLIND/SHEAR COVER OPEN ALARM	TB2-38
CONTACT39	I5.0	LAMP TEST	TB1-39	LIGHT	Q5.4	MAINS FAIL	TB2-39
CONTACT40	I5.1	BLIND/SHEAR COVER OPEN SENSOR	TB1-40	LIGHT	Q5.5	PURGE FAIL	TB2-40
CONTACT41	I5.2	PURGE FAIL	TB1-41	LIGHT	Q5.6	COMMUNICATION FAIL ALARM	TB2-41
CONTACT42	I5.3	MUD PUMP 1 PULS INPUT	TB1-42	LIGHT	Q5.7	PUMP 1 FAULT	TB2-42
CONTACT43	I5.4	MUD PUMP 2 PULS INPUT	TB1-43	LIGHT	Q6.0	PUMP 1 POWER FAIL	TB2-43
CONTACT44	I5.5	MUD PUMP 3 PULS INPUT	TB1-44	LIGHT	Q6.1	PUMP 1 RUN	TB2-44
				LIGHT	Q6.2	PUMP 2 FAULT	TB2-45
PT11	AITR1	CHOKE PRESSURE 1, 20K		LIGHT	Q6.3	PUMP 2 POWER FAIL	TB2-46
PT12	AITR2	CHOKE PRESSURE 2, 20K		LIGHT	Q6.4	PUMP 2 RUN	TB2-47
PT13	AITR3	DRILL PIPE PRESSURE 20K		SOUNDER	Q6.5	ALARM SOUNDER	TB2-48
PT14	AITR4	CASEING PRESSURE 20K		LIGHT	Q6.6	BECON LIGHT	TB2-49
POS1	POS1	POSITION SENSOR 1					
POS2	POS2	POSITION SENSOR 2					
				GAUGE		GAUGE ACCU PRESSURE	TB3-1
				GAUGE		GAUGE MANIFOLD PRESSURE	TB3-2
				GAUGE		GAUGE ANN PRESSURE	TB3-3
				GAUGE		GAUGE AIR PRESSURE	TB3-4
				GAUGE		GAUGE SHEAR BYPASS PRESSURE	TB3-5



Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

QC INSPECTOR (Sign/Date)



Annexure 'F'

MASTER SOFTWARE SECURITY REVIEW PROCEDURE FOR PLC MASTER PANEL

MODEL NO:

**PLEASE ENSURE THAT THE CHECKLIST IS COMPLETE AND
INPUT VOLTAGE CORRECT BEFORE SUPPLYING MAINS
POWER**

PANEL TYPE :

ENCLOSURE SIZE:

SALE ORDER NO:

UNIT NO/JOB NO:

CUSTOMER:

DRAWING NO:

SERIAL NO MASTER PANEL:

**** Before starting the work , Make sure drawing is latest**

S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC System Software (i) PLC User Name/Password.....(Yes/No) (ii) PLC Program write in Flash memory.....(Yes/No) (iii) PLC Software Vaildate..... (Yes/No)						
2	HMI Touch Screen (i) HMI Screen User Name/Password.....(Yes/No) (ii) HMI Software Vaildate.....(Yes/No)						

Workmanship rating----



/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then

Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

Q C INSPECTOR (Sign/Date)



Annexure 'F'

SLAVE PANEL SOFTWARE SECURITY REVIEW PROCEDURE FOR PLC SLAVE PANEL MODEL NO:

PANEL TYPE :

ENCLOSURE SIZE:

SALE ORDER NO:

UNIT NO/JOB NO:

CUSTOMER:

DRAWING NO:

SERIAL NO SLAVE PANEL:

**** Before starting the work , Make sure drawing is latest**

S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC System Software (i) PLC User Name/Password.....(Yes/No) (ii) PLC Program write in Flash memory.....(Yes/No) (iii) PLC Software Vaildate.....(Yes/No)						
2	HMI Touch Screen (i) HMI Screen User Name/Password.....(Yes/No) (ii) HMI Software Vaildate.....(Yes/No)						

Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then



Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

QC INSPECTOR (Sign/Date)



Annexure 'F'

SLAVE PANEL SOFTWARE SECURITY REVIEW PROCEDURE FOR PLC SLAVE PANEL

MODEL NO:

PANEL TYPE :

SALE ORDER NO:

CUSTOMER:

SERIAL NO SLAVE PANEL:

ENCLOSURE SIZE:

UNIT NO/JOB NO:

DRAWING NO:

** Before starting the work , Make sure drawing is latest

S.No	System	Measured Value/Status	Status	Remark (If any)	Date	Done By	Checked By
1	PLC System Software (i) PLC User Name/Password.....(Yes/No) (ii) PLC Program write in Flash memory.....(Yes/No) (iii) PLC Software Vaildate.....(Yes/No)						
2	HMI Touch Screen (i) HMI Screen User Name/Password.....(Yes/No) (ii) HMI Software Vaildate.....(Yes/No)						

Workmanship rating----

/ Satisfactory / Not satisfactory/ Needs improvement /.

If not then



Why.....

TESTED BY (Sign/Date)

ASSEMBLY PERSONNEL

WITNESSED BY (Sign/Date)

Q C INSPECTOR (Sign/Date)



Annexure 'H'

PLC PROGRAMME TRACEABILITY RECORD





SARA SAE ENGINEERING SPECIFICATION

Section: SES 26 – 853

Issue: "A"

Rev No: "2"

Eff. Date: 20-12-2024

Page: 21 of 31



FAILURE MODE EFFECTIVE ANALYSIS (FMEA)

(According to IEC 60812)

DATE:-

PO. NO:-

D.D NO:-

SOFTWARE (REMOTE PANEL)

Before Corrective Action											After Corrective Action							
S.No.	Items/ function	Design Intentions	Potential Mode of Failure	Cause	Local Effects	System Effects	Global Effects	Corrective / Recommended Action	Severity	Detection	Probability Of Occurrence	Risk Priority Number (RPN)	Current Control	Responsibility	Severity	Detection	Occurrence	Risk Priority Number (RPN)
1	Hardware configuration	To Create a hardware configuration in software for physical data processing, sequencing and execution	Program execution fails to start. Program Can't be download.	<ul style="list-style-type: none"> CPU and Modules failure RAM data corruption Hardware configuration errors Wrong Hardware Selection, Hardware Not Installed Properly I/O Moudle Rack Pins Not Fixed Properly 	<ul style="list-style-type: none"> PLC Goes into fault mode and fault LED WILL GLOW 	<ul style="list-style-type: none"> Loss of communication. Loss of well control system functionality Operational shutdown due to system failure. Cascading failure in other system 	<ul style="list-style-type: none"> Delay in well control operations In case of failure hardware modules remote panel will not be able to operate BOP Ram. 	<ul style="list-style-type: none"> Immediate replace the faulty component Create contingency plans for hardware failure Conduct routing inspections and electrical testing 	7	6	4	168	<ul style="list-style-type: none"> Use quality products Verify in FAT Verified hardware configuration in program Critical spare parts are kept on hand to replace any damaged components 	PLC programmer/Assembly department	5	2	3	30
2	Press	To Create a control Program for pressure execution, Convert pressure into an electrical signal and displayed as a digital reading on the gauges and HMI	All Pressure Program execution stops in the CPU.	<ul style="list-style-type: none"> PLC program may be not correct Hardware configuration errors Analog input module may be faulted losse wiring 	<ul style="list-style-type: none"> PLC Goes into fault mode and fault LED WILL GLOW Applicable status indicator is lit on CPU module Wrong Reading can be show on the HMI Screen and Digital Gauges 	<ul style="list-style-type: none"> Loss of ability to see all the pressure of the BOP /diverter Loss of alarm capability for pressure Loss of logging capability of pressure values. 	<ul style="list-style-type: none"> Delay in well control operations Could not see all the pressures of BOP control unit. 	<ul style="list-style-type: none"> Diagnose the problem in PLC program 	6	7	4	168	<ul style="list-style-type: none"> Verify in FAT Verified Pressure Logic in PLC program 	PLC programmer	4	3	3	36
3	FAULT	To Create a control Program for execution of fault alarm, and execute visual and audible on Panels	All alarms in program execution will stop.	<ul style="list-style-type: none"> PLC program may be not correct Ethernet 	<ul style="list-style-type: none"> Inability to see BOP's alarms All alarms execution will stop 	<ul style="list-style-type: none"> Loss of ability to see all the alarms of the BOP /diverter Loss of ability to see low pressure alarms 	<ul style="list-style-type: none"> Delay in well control operations Could not see any alarms 	<ul style="list-style-type: none"> Diagnose the problem in PLC program 	5	5	4	100	<ul style="list-style-type: none"> Verify in FAT Verified Fault Logic in PLC program 	PLC programmer	3	2	3	18





ARA SAE ENGINEERING SPECIFICATION

Section: SES 26 – 853

Issue: "A"

Eff. Date: 20-12-2024

Rev No: "2"

Page: 22 of 31

			Cable can be short.		• Loss of ability to see any fault alarms	of BOP control unit.												
4	IP_OP	To Create a control Program for input/output logic and received signal from sensors/Pressure switches/push button, processes the information and display on remote panels	operation and feedback of four way valve Program execution will stop.	• PLC program may be not correct • Input/Output module may be faulty • losse wiring	• PLC Goes into fault mode and fault LED WILL GLOW • 4-way valve will not operate and feedback of valve position will also not execute	• 4-way valve will not operate for open/block/close • Operational Delays	• Operational inefficiency • Extended downtime • Delay in well control operations	• Diagnose the problem in PLC program	7	6	5	210	• Verify in FAT • Verified Fault Logic in PLC program • Critical spare parts are kept on hand to replace any damaged components	PLC programmer/Assembly department	3	4	4	48
5	HOOTER	To Create a control Program for BOP alarms	In the event horn for alarm in program execution will stop.In This Mode, Sounder can or Cant be stop	• PLC program may be not correct • Rung Can be Short ,Incomplete, or Wrong NO/NC Coil Selected	• Horn will not activate if any alarm appeared	• Loss of ability to hear alarm sound • Loss of alarm capability for low pressure and funcatios fail	• Operational inefficiency	• Diagnose the problem in PLC program	6	6	4	144	• Verify in FAT • Verified Alrms Logic in PLC program	PLC programmer	4	2	3	24
6	VLV_ACT	To Create a control Program for 4-way valve activation.	In the event of a module or rack loss program execution will stop.	• PLC program may be not correct • Rung Can be Short ,Incomplete, or Wrong NO/NC Coil Selected	• Execution of communication of panels will stop • It can possible that some valves operate or Not	• Loss of ability to operate the BOP RAM/diverter (via remote interface only). • Loss of sequencing timing or interlock function • Loss of alarm capability • Loss of logging capability.	• Operational inefficiency • Extended downtime • Delay in well control operations	• Diagnose the problem in PLC program	8	3	4	96	• Verify in FAT • Verified Valve Logic sequencing in PLC program	PLC programmer	5	2	3	30
7	Press	To Create a control Program for pressure execution on remote panels	Preassure Program execution stops.	• PLC program may be not correct • Hardware configuration errors • Analog output module may be faulted • losse wiring	• PLC Goes into fault mode and fault LED WILL GLOW • Applicable status indicator is lit on CPU module	• Loss of ability to see all the pressure of the BOP /diverter • Loss of alarm capability for pressure • Loss of logging capability of pressure • Pressure Values Can be Freeze on the HMI Screen or Digital Gauges	• Operational inefficiency • Loss of ability to see all the Correct pressure values on the HMI Screen	• Diagnose the problem in PLC program • Verify Hardware configuration	7	5	4	140	• Verify in FAT • Verified Pressure Logic in PLC program and hardware configuration	PLC programmer	5	3	3	45



**SARA SAE ENGINEERING SPECIFICATION**

Section: SES 26 – 853

Issue: "A"

Rev No: "2"

Eff. Date: 20-12-2024

Page: 23 of 31

8	VLV_RST	To Create a control Program for BOP alarms reset logic	In the event reset of alarms in program execution will stop.	<ul style="list-style-type: none">PLC program may be not correctRung Can be Short ,Incomplete, or Wrong NO/NC Coil Selected	<ul style="list-style-type: none">All alarms Reset execution will stopAlarms Generate Continously/Frequently	<ul style="list-style-type: none">Loss of ability to reset the alarm of the BOP /diverterUser can not able to stop /identified alarms	<ul style="list-style-type: none">Operational inefficiencyLoss of ability to reset the all alarmsHorn will continues blow	<ul style="list-style-type: none">Diagnose the problem in PLC program	5	5	4	100	<ul style="list-style-type: none">Verify in FATVerified Pressure Logic in PLC program and hardware configuration	PLC programmer	3	3	3	27
9	INPUT	To Create a control Program for input logic and received signal from push button, processes the information and execute on master panel for 4-way valve operation	operation and of four way valve execution will stop.	<ul style="list-style-type: none">PLC program may be not correctInput module may be faultylosse wiring	<ul style="list-style-type: none">PLC Goes into fault mode and fault LED WILL GLOW4-way valve will not operate	<ul style="list-style-type: none">Loss of operation capability of 4-way valve.Can be opertae wrong Selector ValveSelector Valve Can be Work in Reverse direction.	<ul style="list-style-type: none">Operational inefficiencyExtended downtimeDelay in well control operations	<ul style="list-style-type: none">Diagnose the problem in PLC program	7	4	5	140	<ul style="list-style-type: none">Verify in FATVerify PLC program in INPUT blockVerify Input and module hardwareCritical spare parts are kept on hand to replace any damaged components	PLC programmer	3	2	3	18
10	OUTPUT	To Create a control Program for output logic and received signal from master control panel of 4-way valves and alarm status	Feedback of four way valve execution will stop.	<ul style="list-style-type: none">PLC program may be not correctOutput module may be faultylosse wiring	<ul style="list-style-type: none">PLC Goes into fault mode and fault LED WILL GLOWFeedback of 4-way valve position will also not execute	<ul style="list-style-type: none">Loss of capability to see the position of 4-way valveCan be operate wrong Selector Valve or Regulator, Selector Valve / Regulator Can be Work in Reverse directionThis Can be Possible the Wrong Selector Valve Feedback and alarms appear on the Remotes Panels	<ul style="list-style-type: none">Operational inefficiencyLoss of ability to see 4-way valve position,alarmsDelay in well control operations	<ul style="list-style-type: none">Diagnose the problem in PLC program	7	4	5	140	<ul style="list-style-type: none">Verify in FATVerify PLC program in INPUT blockVerify Outputt and module hardwareCritical spare parts are kept on hand to replace any damaged components	PLC programmer	3	2	3	18



**SARA SAE ENGINEERING SPECIFICATION**

Section: SES 26 – 853

Issue: "A"

Rev No: "2"

Eff. Date: 20-12-2024

Page: 24 of 31

11	VLV_CON	To Create a control Program for bop 4-way valve configuration	In the event program execution will stop. In this Mode, Execution of communication rung stop	• PLC program may be not correct. • Rung Can be Short, Incomplete, or Wrong NO/NC Coil Selected	• Impaired BOP functionality • Inability to operate 4-way valve from remote panels • Lack of 4-way valve status visibility • Inability to detect BOP alarms • Execution of communication of panels will stop	• Loss of operation capability of 4-way valve. • Loss of capability to see the position of 4-way valve • Loss of sequencing timing or interlock function; loss of alarm capability • Loss of logging capability. • Pressure Values Can be Freeze on the HMI Screen or digital gauges • Alarms Generate Continuously/Frequently • User can not able to stop /identified alarms Data Communication Between Panels Breaks	• Operational inefficiency • Loss of operation capability of 4-way valve. • Loss of capability to see the position of 4-way valve position, alarms • Delay in well control operations	• Diagnose the problem in PLC program	8	6	4	192	● Verify in FAT ● Verify in PLC program in VLV_ACT block	PLC programmer	5	4	3	60
----	---------	---	--	---	--	--	---	---------------------------------------	---	---	---	-----	--	----------------	---	---	---	----





SARA SAE ENGINEERING SPECIFICATION

Section: SES 26 – 853

Issue: "A"


Rev No: "2"

Eff. Date: 20-12-2024

Page: 25 of 31

		Before Corrective Action	After Corrective Action
1	<ul style="list-style-type: none">• CPU and Modules failure• RAM data corruption• Hardware configuration errors• Wrong Hardware Selection, Hardware Not Installed Properly• I/O Moudle Rack Pins Not Fixed Properly	168	30
2	<ul style="list-style-type: none">• PLC program may be not correct• Hardware configuration errors• Analog input module may be faulted• losse wiring	168	36
3	<ul style="list-style-type: none">• PLC program may be not correct• Ethernet Cable can be short.	100	18
4	<ul style="list-style-type: none">• PLC program may be not correct• Input/Output module may be faulty• losse wiring	210	48
5	<ul style="list-style-type: none">• PLC program may be not correct• Rung Can be Short, Incomplete, or Wrong NO/NC Coil Selected	144	24
6	<ul style="list-style-type: none">• PLC program may be not correct• Rung Can be Short, Incomplete, or Wrong NO/NC Coil Selected	96	30
7	<ul style="list-style-type: none">• PLC program may be not correct• Hardware configuration errors• Analog output module may be faulted• losse wiring	140	45
8	<ul style="list-style-type: none">• PLC program may be not correct• Rung Can be Short, Incomplete, or Wrong NO/NC Coil Selected	100	27

Risk Priority (RPN) Control System for Surface BOP Stack



**SARA SAE ENGINEERING SPECIFICATION****Section: SES 26 – 853****Issue: "A"****Rev No: "2"****Eff. Date: 20-12-2024****Page: 26 of 31**

9	● PLC program may be not correct ● Input module may be faulty ● losse wiring	140	18
10	● PLC program may be not correct ● Output module may be faulty ● losse wiring	140	18
11	● PLC program may be not correct ● Rung Can be Short ,Incomplete, or Wrong NO/NC Coil Selected	192	60





SARA SAE ENGINEERING SPECIFICATION
Section: SES 26 – 853
Issue: "A"
Rev No: "2"
Eff. Date: 20-12-2024
Page: 27 of 31

An EKAASAI Enterprise
FAILURE MODE EFFECTIVE ANALYSIS (FMEA)
 (According to IEC 60812)

DATE:-
PO. NO:-
D.D NO:-
HARDWARE (REMOTE PANEL)

S.No.	Items/ function	Design Intentions	Before Corrective Action							After Corrective Action								
			Potential mode of Failure	Cause of failure	Local Effects	System Effects	Global Effects	Corrective / Recommended Action	Severity	Detection	Probability Of Occurrence	Risk Priority Number (RPN)	Current Control	Responsibility	Severity	Detection	Occurrence	Risk Priority Number (RPN)
1	Proximity Sensor	Feedback of 4-way valve position.	Feedback of four way valve execution will stop.	<ul style="list-style-type: none"> Proximity Sensor may be faulty connection loose between proximity Sensor to amplifier Disc detaint pointer may not come within sensor range 	<ul style="list-style-type: none"> Inability to detect position of 4-way valves Loss of local Monitoring 	<ul style="list-style-type: none"> Loss of capability to see the position of 4-way valve. Degraded efficiency 	<ul style="list-style-type: none"> Delay in well control operations Legal and Regulatory Consequences 	<ul style="list-style-type: none"> Replace the Faulty Proximity Sensor Upgrade Sensor system Inspect the wiring and connections Conduct routine inspections Adjustment disc detaint pointer 	7	3	4	84	<ul style="list-style-type: none"> Verified in FAT Use Quality products Experienced workers will do the Assembly and connections 	Assembly department.	5	2	3	30
2	Solenoid valve	Operation of 4-way valves (Open/Block/Close)	Operation of 4-way valve will stop from Driller/Tool pusher panels	<ul style="list-style-type: none"> Solenoid valve may be faulty connection loose between Solenoid valve to PLC modules 	<ul style="list-style-type: none"> Inability to operate 4-way valves Operational disruptions Impaired BOP functionality 	<ul style="list-style-type: none"> Loss of well control system functionality Increased downtime for unplanned repairs 	<ul style="list-style-type: none"> Delay in well control operations increased risk of blowout In case of failure solenoid valve will not be able to operate BOP rams open/close 	<ul style="list-style-type: none"> Immediately replace the faulty component Inspect the wiring and connections Check the air filter of solenoid valve input line 	7	5	4	140	<ul style="list-style-type: none"> Verified in FAT Use Quality products Circuit protection, Testing Spare part list 	Assembly department.	4	2	3	24
3	Push button	Giving Signal to operate 4-way valve funcations (Open/Block/Close)	Inability to Activate BOP Functions from remote control pnaels	<ul style="list-style-type: none"> Pushbutton may be faulty connection loose between push button to PLC modules Faulty Actuation mechanism 	<ul style="list-style-type: none"> Partial or complete failure of specific BOP functions. Operational disruptions 	<ul style="list-style-type: none"> 4-way valve will not operate for open/block/close Operational Delays 	<ul style="list-style-type: none"> Operational inefficiency Extended downtime 	<ul style="list-style-type: none"> Immediately replace the faulty component Inspect the wiring and connections 	7	5	4	140	<ul style="list-style-type: none"> Verified in FAT Item must be in stock. Party recommended spare part list. 	Assembly department.	3	2	3	18
4	Pilot light	Indicates the 4-way valve positions either open,block or close	Indability to see 4-way valve position on remote control panels (open/block/close)	<ul style="list-style-type: none"> Pilot light may be faulty connection loose between pilot light to PLC modules LED may be burned 	<ul style="list-style-type: none"> Inability to detect 4-way valve positions Operational disruptions 	<ul style="list-style-type: none"> Loss of well control system functionality Increased downtime for unplanned repairs 	<ul style="list-style-type: none"> Compromised well control degraded efficiency missed preventive maintenance triggers 	<ul style="list-style-type: none"> Immediately replace the faulty component Inspect the wiring and connections 	7	3	4	84	<ul style="list-style-type: none"> Verified in FAT Item must be in stock. Party recommended spare part list. 	Assembly department.	5	2	3	30




SARA SAE ENGINEERING SPECIFICATION
Section: SES 26 – 853
Issue: "A"
Rev No: "2"
Eff. Date: 20-12-2024
Page: 28 of 31

5	Digital Gauge	Receive electrical signal from Transducer and displayed as a digital reading on the gauge's screen	Inability to see pressure reading on remote control panels	<ul style="list-style-type: none"> Digital Gauge may be faulty • Loose wiring • Excessive vibration • Extreme Temperature 	<ul style="list-style-type: none"> Inability to see pressure reading • Localized failure of BOP operations • Operational disruptions 	<ul style="list-style-type: none"> Loss of well control system functionality • Undetected failure leading to cascading system issues • Reduced safety margins 	<ul style="list-style-type: none"> Safety and Well Control Risks 	<ul style="list-style-type: none"> Immediately replace the faulty component • Inspect the wiring and connections • perform system pressure test • Verify pressure readings on digital gauges 	7	4	4	112	<ul style="list-style-type: none"> • Verified in FAT • Proper surging to reduce vibrations • Use quality product • Party recommended spare part list. 	Assembly department.	4	2	3	24
6	Amplifier	Low signal received from sensors and give to plc modules with amplify signal.	Feedback of four way valve execution will stop.	<ul style="list-style-type: none"> Proximity Sensor may be faulty • connection loose between proximity Sensor to amplifier • Amplifier may be faulty 	<ul style="list-style-type: none"> Inability to detect position of 4-way valves • Loss of local Monitoring 	<ul style="list-style-type: none"> Loss of capability to see the position of 4-way valve. • Degraded efficiency 	<ul style="list-style-type: none"> Delay in well control operations • Legal and Regulatory Consequences 	<ul style="list-style-type: none"> Replace the Faulty • Inspect the wiring and connections • Cunduct routine inspections • Verify the input voltage 	7	3	4	84	<ul style="list-style-type: none"> • Verified in FAT • Use Quality products • Experienced workers will do the Assembly and connections • Party recommended spare part list. 	Assembly department.	5	2	3	30
7	Pressure Swtich	Feedback of 4-way valve position.	Feedback of four way valve execution will stop.	<ul style="list-style-type: none"> Pressure switch may be faulty • Wiring fault or loose connections • Sunbber oil may be jammed • Adjustment wheel may be not set properly 	<ul style="list-style-type: none"> Inability to detect position of 4-way valves • Loss of local Monitoring 	<ul style="list-style-type: none"> Loss of capability to see the position of 4-way valve. • Degraded efficiency 	<ul style="list-style-type: none"> Delay in well control operations • Legal and Regulatory Consequences 	<ul style="list-style-type: none"> Replace the Faulty Pressure switch • inspect and clean sanubber oil • Inspect the wiring and connections • Cunduct routine inspections • Adjustment pressure switch wheel 	7	4	4	112	<ul style="list-style-type: none"> • Verified in FAT • Use Quality products • Experienced workers will do the Assembly and connections 	Assembly department.	4	2	3	24
8	Pressure Transducer	Convert pressure into an electrical signal and displayed as a digital reading on the gauge's screen	Inability to see pressure reading on remote control panels	<ul style="list-style-type: none"> Pressure transducer may be faulty • Loose wiring • Sunbber oil may be jammed 	<ul style="list-style-type: none"> Inability to see pressure reading on remote panels • Localized failure of BOP operations • Operational disruptions 	<ul style="list-style-type: none"> Loss of well control system functionality • Undetected failure leading to cascading system issues • Reduced safety margins 	<ul style="list-style-type: none"> Safety and Well Control Risks 	<ul style="list-style-type: none"> Immediately replace the faulty component • Inspect the wiring and connections • perform system pressure test • Verify pressure readings on digital gauges • inspect and clean sanubber oil 	7	4	4	112	<ul style="list-style-type: none"> • Verified in FAT • Use quality product • Critical spare parts are kept on hand to replace any damaged components 	Assembly department.	4	2	3	24
9	Purge	To prevent explosion in hazardous areas by continuously removing potentially flammable gases from the system	Reduced system readiness and safety	<ul style="list-style-type: none"> Purge may be faulty • Air supply failure • Insufficient air supply 	<ul style="list-style-type: none"> Flammable Gases Can be enter inside the Panels. • Short circuit or PLC System can be Burn or Failure 	<ul style="list-style-type: none"> Degraded efficiency • BOP control system failure 	<ul style="list-style-type: none"> Safety and Well Control Risks • Regulatory and Legal Consequences 	<ul style="list-style-type: none"> Repair or Replace Faulty Components • Compressor with sufficient air supply 	5	3	4	60	<ul style="list-style-type: none"> Critical spare parts are kept on hand to replace any damaged components 	Assembly department.	3	2	3	18



**SARA SAE ENGINEERING SPECIFICATION**

Section: SES 26 – 853

Issue: "A"

Eff. Date: 20-12-2024


Rev No: "2"

Page: 29 of 31

10	PLC CPU and it's module	Receives input signal from sensors/Pressure switches/push button, processes the information and control devices	Inability to Activate BOP Functions form remote control panels and monitor 4-way valve position, pressure readings, alarms	<ul style="list-style-type: none">• Frequent power outage or fluctuations• Input/Output (I/O) module disconnected between CPU• Communication Break• Connection loose between PLC modules• PLC CPU and it's module may be faulty	<ul style="list-style-type: none">• Complete failure of BOP functions.• Operational disruptions• Personnel injuries or fatalities• Evacuation delays• Inability to operate 4-way valves• Inability to detect position of 4-way valves• Loss of local Monitoring	<ul style="list-style-type: none">• Loss of well control system functionality• 4-way valve will not operate for open/block/close• Operational Delays• Loss of capability to see the position of 4-way valve.• Communication Breakdown of Valves Remote operation, Alarm & indication.	<ul style="list-style-type: none">• Blowout Risk• Operational Delays and Financial Loss• Regulatory Compliance Issues	<ul style="list-style-type: none">• Immediate Diagnosis• Repair or Replace Faulty Components• Check Communication Links• Power Supply Inspection• Inspect the wiring and connections• Conduct routine inspections	8	2	4	64	<ul style="list-style-type: none">• Verified in FAT• Simulate the failure condition & check the redundant working of both panel.• Software validation to be verified• Experienced workers will do the Assembly and connections• Party recommended spare part list.	PLC programmer/Assembly department.	5	1	3	15



		Before Corrective Action	After Corrective Action
1	<ul style="list-style-type: none"> • Proximity Sensor may be faulty • connection loose between proximity Sensor to amplifier • Disc detent pointer may not come within sensor range 	84	30
2	<ul style="list-style-type: none"> • Solenoid valve may be faulty • connection loose between Solenoid valve to PLC modules 	140	24
3	<ul style="list-style-type: none"> • Pushbutton may be faulty • connection loose between push button to PLC modules • Faulty Actuation mechanism 	140	18
4	<ul style="list-style-type: none"> • Pilot light may be faulty • connection loose between pilot light to PLC modules • LED may be burned 	84	30
5	<ul style="list-style-type: none"> • Digital Gauge may be faulty • Loose wiring • Excessive vibration • Extreme Temerature 	112	24
6	<ul style="list-style-type: none"> • Proximity Sensor may be faulty • connection loose between proximity Sensor to amplifier • Amplifier may be faulty 	84	30



**SARA SAE ENGINEERING SPECIFICATION****Section: SES 26 – 853****Issue: "A"****Rev No: "2"****Eff. Date: 20-12-2024****Page: 31 of 31**

7	● Pressure switch may be faulty ● Wiring fault or loose connections ● Sunbber oil may be jammed ● Adjustment wheel may be not set properly	112	24
8	● Pressure transducer may be faulty ● Loose wiring ● Sunbber oil may be jammed	112	24
9	● Purge may be faulty ● Air supply failure ● Insufficient air supply	60	18
10	● Frequent power outage or fluctuations ● Input/Output (I/O) module disconnected between CPU ● Communication Break ● Connection loose between PLC modules ● PLC CPU and it's module may be faulty	64	15



Annexure 'H'
PLC PROGRAM TRACEABILITY RECORD

CUSTOMER	
JOB NO.	
UNIT NO.	
PLC PROGRAM NO.	
PLC MANUFACTURER	
PLC MODEL	
PROGRAMMING SOFTWARE	
SOFTWARE VERSION	
PROGRAM DEVELOPMENT DATE & TIME	
PROGRAM DEVELOPMENT LOGIC	
COMMUNICATION SYSTEM	
PROGRAM USER ID	
PROGRAM PASSWORD	

Name:	Name:	Name:
Program Prepared By:	Program Reviewed By:	Program Approved By:

➤ *IF ANY MODIFICATION ARE REQUIRED IN THE PROGRAM, PLEASE PROVIDE THE NECESSARY DETAILS IN THE SECTION BELOW*

PROGRAM CHANGE DATE & TIME	
REASON FOR PROGRAM CHANGE	
DETAILED DESCRIPTION OF CODE DIFFERENCES	

Name:	Name:	Name:
Program Prepared By:	Program Reviewed By:	Program Approved By:

